

XD1210T4



1200V 10A SiC Schottky Barrier Diode in TO-247-3L Package

Datasheet version: 1.0 Preliminary

Features

BV_{dss}	I_f (135°C) **	I_f (145°C) **	Q_C^*
1200 V	14A	10 A	27 nC

- No reverse recovery
- High speed switching
- Low switching losses
- Positive temperature coefficient



Applications

- Switching Power Supplies
- Adapters, Quick Chargers
- Power Factor Corrections
- Motor Drives

Description

- These devices are 1200 SiC Schottky Barrier Diodes (SBD) with zero reverse recovery that allows systems to operate at higher switching frequencies. Lower heat dissipation requirements and higher system efficiency can be achieved in this TO-247-3L package.

Device Characteristics

Static Parameters				Test data			
	Sym.	Parameters	Conditions	Min	Typical	Max	Unit
1	V _{DC}	DC Blocking Voltage	I _R =100 μA	1200	/	/	V
2	V _F	Forward Voltage	I _F =5A, T _j =25°C	/	1.4	1.8	V
			I _F =5A, T _j =175°C	/	2.1	2.7	
3	I _R	Reverse Current	V _R =1200V, T _j =25°C	/	3	15	μA
			V _R =1200V, T _j =175°C	/	15	100	
4	C	Total Capacitance	V _R =0V, f=1MHz	/	353	/	pF
			V _R =400V, f=1MHz	/	25.8	/	
			V _R =800V, f=1MHz	/	20.0	/	
5	Q _C	Total capacitive charge	V _R =800V	/	27.0	/	nC
6	E _C	Capacitance Stored Energy	V _R =800V	/	7.9	/	μJ
Thermal Parameters				Test data			
	Sym.	Parameters	Conditions	Min	Typical	Max	Unit
1	R _{th(j-c)}	Thermal resistance	Per device	/	1.6*/0.8**	/	°C/w

** Per device * Per leg


Absolute Max. Ratings

	Symbols	Parameters	Test Conditions	Value	Unit
1	V_{RR-max}	Reverse Voltage (Repetitive Peak)	$T_C = 25^\circ C$	1200	V
2	V_{RS-max}	Reverse Voltage (Surge Peak)	$T_C = 25^\circ C$	1200	V
3	V_{dc-max}	Reverse Voltage (DC)	$T_C = 25^\circ C$	1200	A
4	I_{F-max}	Continuous Forward Current	$T_C = 25^\circ C$	15/30	A
			$T_C = 135^\circ C$	7.3/14	
			$T_C = 155^\circ C$	5.0/10	
5	I_{FS-max}	Non-repetitive Forward Current (Surge)	$T_C = 25^\circ C$ $t_p = 10ms$ Half Sine Pulse	63*	A
6	$P_{total-max}$	Total Power Dissipation	$T_C = 25^\circ C$	91*	W
7	$\int i^2 dt$ $_{max}$	i^2t value	$T_C = 25^\circ C$ $t_p = 10ms$	20*	A ² s
8	T_{o-max}	Operation Temperature	/	-55 to 175	°C
9	$T_{s-storage}$	Storage temperature	/	-55 to 175	°C
10	M	Mounting Torque	M3 Screw	1	Nm


Ordering

Order Code	Package Type	Packaging Method	Qty
XD1210L3	TO-247F-3L	Tube	300


Electrical Performance




Forward Characteristics




Reverse Characteristics




Current Derating




Capacitance vs. V_R



Power Derating




Capacitance Stored Energy



Total Capacitance Charge vs. V_R



Package Information



SYMBOL	mm		
	MIN	NOM	MAX
A	4.8	5	5.2
A1	2.21	2.41	2.61
A2	1.85	2	2.15
b	1.11	1.21	1.36
b2	1.91	2.01	2.21
b4	2.91	3.01	3.21
c	0.51	0.6	0.75
D	20.7	21	21.3
D1	16.25	16.55	16.85
D2	1	1.2	1.35
E	15.5	15.8	16.1
E1	13	13.3	13.6
E2	4.8	5	5.2
E3	2.3	2.5	2.7
e	5.44 BSC		
L	19.62	19.92	20.22
L1	-	-	4.3
ϕP	3.4	3.6	3.8
$\phi P1$	-	-	7.3
Q	5.4	5.8	6.2
S	6.20 BSC		